

EK SD 50 ML Electromechanical Stripping Tool 6 - 35 mm²



K50
SERIE



- ▶ The Klauke micro with intuitive PowerSense function makes it easy to strip all common types of conductor with the convenience of an electromechanical tool
- ▶ One tool for all common insulation types
- ▶ Replacing inserts is fast and easy
- ▶ Fast and effortless stripping and cutting
- ▶ Excellent stripping results with minimal effort
- ▶ More than 30 inserts for crimping, stripping and cutting

Characteristics

- Simple and safe: One-button operating concept for controlling all tool functions
- PowerSense function: Manual pre-clamping, motorized crimping
- Electronic control with locking function monitors full closing of the dies
- Ergonomic 2C housing in the Klauke „In-line Design“
- Tool fixing point for use with balancer aid or lanyard
- Very low weight and high speed for maximum efficiency
- Powerful drive technology for effortless operations
- Powerful 10.8 V Li-Ion battery with charge status display
- LED for work area illumination
- Maintenance display via LED

Suitable for

- 50-series interchangeable dies

Technical data	
Stripping range	6 - 35 mm ²
Stripping length	up to 28 mm
Cutting range	up to 11.5 mm diameter
Battery voltage	10,8 V
Battery capacity	2,5 Ah, Li-Ion
Charging time	approx. 45 min.
Weight incl. battery	0,96 kg
Ambient temperature	-10 °C up to +40 °C
Conductor classes	1 - Single-stranded round conductor 2 - Multi-stranded round conductor 5 - Fine-stranded round conductor 6 - Ultra fine-stranded round conductor

Item	Part No.
Electromechanical Stripping Tool 6 - 35 mm ²	EKSD50ML
Scope of supply	Part No.
Battery 10,8 V / 2,5 Ah, Li-Ion (27 Wh)	RAML1225
Charger for 10.8 V Li-Ion batteries, 230V	LGL1
Stripping insert 10 mm ²	SD5010
Stripping insert 16 mm ²	SD5016
Stripping insert 25 mm ²	SD5025
Stripping insert 35 mm ²	SD5035
Cable stop	SD50CS
Plastic case	KKEK50ML
Accessories	Part No.
Stripping insert 6 mm ²	SD5006

Klauke®

